

Tiger CUB

**Compact,
manueverable,
unbeatable.**



Specifications

Engine Options:

- 19hp Kawasaki, air-cooled, twin cylinder, vertical shaft
- 23hp Kohler, air-cooled, twin cylinder, vertical shaft
- 25hp Kohler, air-cooled, twin cylinder, vertical shaft*
- 26hp Briggs & Stratton ELS, air-cooled, twin cylinder, vertical shaft*

Fuel Capacity/Design:

8 gallons, dual fuel tanks with molded-in cupholder.

Travel Control:

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.*

Ground Speed:

10mph forward, 4.5mph reverse

Main Frame Construction:

Steel tube frame, full-length, fully-welded

Drive Tires:

- 23 x 9.5 -12, 4 ply (48" & 52" models)
- 24 x 12 - 12, 4 ply (61" models)

Caster Tires:

- 13 x 5 - 6, 4 ply; Flat-Free, semi-pneumatic* (48" & 52" models)
- 13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic* (61" models)

Caster Wheel Bearings:

Tapered roller bearings

Front Caster Arm Design:

Bolt-on for easy replacement if necessary

Hydraulic Pumps:

Dual Pumps; 10cc displacement, Hydro-Gear

Hydraulic Oil Cooler:

Not required - Large capacity cooling reservoir

Hydraulic Oil Filter:

10 micron

Hydraulic Wheel Motors:

Dual Hydro-Gear/Danfoss 15ci heavy-duty motors with extra large shafts

Electrical System:

12 Volt battery, 300 cca. Solenoid shift starter.

Belts:	Kevlar cord. Self-adjusting, spring-loaded, self-tightening
Drive/Load Pulleys:	Split-steel design -- stronger and lighter weight than cast-iron
Instrument Panel :	Key switch, throttle, manual choke, BBC switch
Seat:	Adjustable, fully cushioned seat with padded arm rests & retractable seat belt.
PTO - Electric Clutch:	Ogura GT3.5 - 250 ft lb / adjustable air-gap
Cutter Decks:	48", 52", & 61" Velocity Plus Decks. Floating, adjustable, anti-scalping design.
Cutter Deck Construction:	Tri-Plate, welded with 7 gauge deck shell, 10 gauge & 11 gauge reinforcement plates.
Cutter Deck Drive:	Belt driven -- Straight belt for long life, not a twisted "mule" drive
Number of Anti-Scalp Wheels:	<ul style="list-style-type: none"> • 48": 4 wheels in 4 positions • 52": 4 wheels in 4 positions • 61": 7 wheels in 5 positions
Cutter Deck Spindles:	Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
Cutter Deck Height Adjustment:	Foot pedal lift with self-locking mechanism at transport position
Cutting Range:	1-1/4" to 5-1/2" in 1/4" increments
Number of Cutter Blades:	3 Marbain blades
Total Length:	<ul style="list-style-type: none"> • 48" & 52" models: 80" • 61" models: 83"
Total Width (with discharge chute in mowing position):	<ul style="list-style-type: none"> • 48" models: 60.5" • 52" models: 64.5" • 61" models: 73.5"
Total Width (with discharge chute in transport position):	<ul style="list-style-type: none"> • 48" models: 49" • 52" models: 53" • 61" models: 62"
Height (with ROPS):	66"
Height (with ROPS folded*):	54"
Weight (with ROPS):	<ul style="list-style-type: none"> • 48" models: 1030-1050 lbs. • 52" models: 1100 lbs. • 61" models: 1150 lbs.
Warranty:	<ul style="list-style-type: none"> • 2 Yr. Mower Warranty—Parts & labor. • 3 Yr. Deck Warranty—First & second years parts & labor; third year parts. • 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts. • 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



**Tiger
CUB**

* STC48V-26BS, STC52V-25CV, and STC61V-25CV models include non-foldable ROPS, pneumatic (air-filled) front caster tires, and regular control levers. See your Scag dealer for more information.



All specifications subject to change without notice.

WWW.SCAG.COM