



# DUAL-FUEL

**SCAG**  
POWER EQUIPMENT

# TURF Tiger

**Dual-Fuel flexibility  
with the flip of a switch.**

## Specifications

**Engine:**

Kubota Dual-Fuel, in-line 3 cylinder, liquid-cooled, 29hp propane / 31hp gasoline. Just flip a switch to change from gasoline power to propane, even while the engine is running.

**Fuel Capacity/Design:**

- Gasoline: 11 gallons, single fuel tank mounted low in the center of the mower to lower the center-of-gravity and improve hillside stability and traction
- Propane: 15.8 gallons / 67 lb. total propane capacity (two 7.9 gal. / 33.5 lb. tanks); two standard industrial LP tanks mounted above the fenders

**Travel Control:**

Twin "Quick-Fit" steering controls with gas dampers for smooth, precise maneuverability. Adjustable to fit various operator sizes.

**Ground Speed:**

11mph forward, 5 mph reverse

**Main Frame Construction:**

Double tube, steel frame, full-length, fully-welded

**Drive Tires:**

24 x 12 - 12, 4 ply

**Caster Tires:**

13 x 6.5 - 6, 4 ply; Flat-Free, semi-pneumatic

**Caster Wheel Bearings:**

Tapered roller bearings

**Front Caster Arm Design:**

Bolt-on for easy replacement if necessary

**Hydraulic Pumps:**

Dual Pumps; 16cc displacement, Hydro-Gear

**Hydraulic Oil Cooler:**

Yes - 4 qt system capacity with auxiliary oil cooler

**Hydraulic Oil Filter:**

10 micron

**Hydraulic Wheel Motors:**

Dual 18ci Hydro-Gear cast-iron high torque wheel motors

**Electrical System:**

12 Volt battery, 525 cca. Alternator, 40 amp charging. Solenoid shift starter.

**WWW.SCAG.COM**

(Continued)

**SCAG**

- Belts:** Kevlar cord. Self-adjusting, spring-loaded, self-tightening
- Drive/Load Pulleys:** Split-steel design -- stronger and lighter weight than cast-iron
- Instrument Panel :** Ammeter, key switch, throttle, manual choke, BBC switch, water temp gauge
- Command-Comfort Operator's Station:**
- Torsion spring suspension seat, fully adjustable, with arm rests
  - "Quick-Fit" steering control levers feature incredible range of adjustment for optimal comfort and control
  - 3-Position adjustable deck lift foot pedal allows for easy deck lift for all operators
- PTO - Electric Clutch:** Ogura GT3.5 - 250 ft lb / adjustable air-gap
- Cutter Decks:** 61" Velocity Plus deck. Floating, adjustable, anti-scalping design.
- Cutter Deck Construction:** Tri-Plate, welded with 10 gauge top, 7 gauge skirts, 7 gauge & 11 gauge reinforcement plates.
- Cutter Deck Drive:** Drive shaft driven -- eliminates belt slip for increased reliability & longevity
- Number of Anti-Scalp Wheels:** 9 wheels in 7 positions
- Cutter Deck Spindles:** Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty
- Cutter Deck Height Adjustment:** Foot pedal lift (3-position adjustable) with self-locking mechanism at transport position
- Cutting Range:** 1" to 6" in 1/4" increments
- Number of Cutter Blades:** 3 Marbain blades
- Total Length:** 87.5"
- Total Width (with discharge chute in mowing position):** 73.5"
- Total Width (with discharge chute in transport position):** 62"
- Height (with ROPS):** 67.5"
- Height (with ROPS folded):** 56.5"
- Weight (with ROPS):** 1540 lbs
- Warranty:**
- 2 Yr. Mower Warranty—Parts & labor.
  - 3 Yr. Deck Warranty—First & second years parts & labor; third year parts.
  - 3 Yr. Spindle Warranty—First & second years parts & labor; third year parts.
  - 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.



All specifications subject to change without notice.

[WWW.SCAG.COM](http://WWW.SCAG.COM)