

**V-RIDE*****Stand up for productivity!*****Specifications****Engine Options:**

- 20hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 24hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 26hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft
- 29hp Kawasaki FX, air-cooled, twin cylinder, vertical shaft

**Fuel Capacity/Design:**

- 5.5 gallons, single tank with top-mounted fuel shutoff valve (36" & 48")
- 8 gallons, single tank with top-mounted fuel shutoff valve (52" & 61")

**Travel Control:**

Twin lever steering controls for smooth, precise maneuverability

**Ground Speed:**

- Up to 7.7 mph forward (36" model), 6 mph reverse
- Up to 8.5 mph forward (48" & 52" models), 6 mph reverse
- Up to 11 mph forward (61" model)

**Drive Tires:**

- 18 x 7 - 8, 4 ply (36" model)
- 20 x 10.5 - 8, 4 ply (48", 52" & 61" models)

**Caster Tires:**

11 x 4 - 5, Flat-Free, semi-pneumatic

**Caster Wheel Bearings:**

Tapered roller bearings

**Hydraulic Pumps:**

Dual Pumps; 10cc displacement (12cc on 61"), Hydro-Gear

**Hydraulic Wheel Motors:**

Dual 12ci heavy-duty motors with extra large shafts

**Hydraulic Oil Cooling:**

- Auxiliary oil cooler (48", 52" & 61" models)
- Large capacity cooling reservoir (all models)

**Hydraulic Oil Filter:**

10 micron

**Belts:**

Kevlar cord. Self-adjusting, spring-loaded, self-tightening

**Drive/Load Pulleys:**

Split-steel design -- stronger and lighter weight than cast-iron

|  |  |
|--|--|
| <b>Instrument Panel :</b>                                      | Key switch, throttle, manual choke, BBC switch, digital hour meter, neutral lock lever   |
| <b>Operator Platform:</b>                                      | Heavy gauge steel with extruded star pattern for no-slip footing. Rear portion of the platform can be folded forward to reduce overall machine length by 4". Coil suspension under platform utilizes 3.5 inch springs; 1.25 inches of suspension travel.   |
| <b>Operator Comfort Pad:</b>                                   | Adjustable to 12 different positions to fit a wide range of operator sizes and riding styles   |
| <b>PTO - Electric Clutch:</b>                                  | Heavy-duty Ogura PTO clutch brake with adjustable air-gap  |
| <b>Cutter Decks:</b>   | 36" Advantage deck; 48", 52" & 61" Velocity Plus decks. Floating, adjustable, anti-scalping design.  |
| <b>Cutter Deck Construction:</b>                               | Tri-Plate, fully-welded: 36" & 48" with 7 gauge deck top and skirt, 10 gauge and 11 gauge reinforcement plates; 52" with 10 gauge top, 7 gauge skirt, 10 gauge and 11 gauge reinforcement plates; 61" with 10 gauge top, 7 gauge skirt, 7 gauge and 11 gauge reinforcement plates.   |
| <b>Number of Anti-Scalp Wheels:</b>                            | <ul style="list-style-type: none"> <li>• 36": 4 wheels in 3 positions</li> <li>• 48": 5 wheels in 3 positions</li> <li>• 52": 7 wheels in 5 positions</li> <li>• 61": 9 wheels in 7 positions</li> </ul>   |
| <b>Cutter Deck Spindles:</b>                                   | Scag Heavy-Duty Spindles w/cast-iron housing & tapered roller bearings, backed by 3-year limited warranty  |
| <b>Cutter Deck Height Adjustment:</b>                          | Hand lever lift with self-locking mechanism at transport position  |
| <b>Cutting Range:</b>  | 1-1/2" to 4-1/2" in 1/4" increments  |
| <b>Number of Cutter Blades:</b>                                | 3 Marbain blades   |
| <b>Total Length:</b>   | <ul style="list-style-type: none"> <li>• 36" models: 71"</li> <li>• 48" models: 69.5"</li> <li>• 52" models: 71.75"</li> <li>• 61" models: 75.5"</li> </ul>  |
| <b>Total Width - with discharge chute in mowing position):</b> | <ul style="list-style-type: none"> <li>• 36" models: 47.75"</li> <li>• 48" models: 61.25"</li> <li>• 52" models: 65.25"</li> <li>• 61" models: 74.25"</li> </ul>   |
|  | <ul style="list-style-type: none"> <li>• 36" models: 37.25"</li> <li>• 48" models: 49.75"</li> <li>• 52" models: 53.75"</li> <li>• 61" models: 62.75"</li> </ul>   |
| <b>Height:</b>   | <ul style="list-style-type: none"> <li>• 36" models: 46.5"</li> <li>• 48"/52"/61" models: 47.5"</li> </ul>   |
| <b>Weight:</b>   | <ul style="list-style-type: none"> <li>• 36" models: 775 lbs.</li> <li>• 48"/52" models: 860 lbs.</li> <li>• 61" models: 975 lbs.</li> </ul>   |
| <b>Warranty:</b>   | <ul style="list-style-type: none"> <li>• 2 Yr. Commercial Mower Warranty—Parts &amp; labor.</li> <li>• 3 Yr. / 500 Hour Non-Commercial Mower Warranty—Parts &amp; labor.</li> <li>• 3 Yr. Deck Warranty—First &amp; second years parts &amp; labor; third year parts.</li> <li>• 3 Yr. Spindle Warranty—First &amp; second years parts &amp; labor; third year parts.</li> <li>• 2 Yr. Engine Warranty—Minimum two-year warranty covered directly through the individual engine manufacturer.</li> </ul> |



All specifications subject to change without notice.

**WWW.SCAG.COM**